

BS 7889

XLPE Insulated, PVC Sheathed Single Core Cable. BS 7889. 600/1000 V



Prysmian BS 7889 is an unarmoured industrial single core wiring cable with cross linked polyethylene insulation and PVC sheath.

KEY APPLICATIONS

Suitable for installation in areas with reduced risk of mechanical damage; on tray, in free air or clipped direct. Suitable also for conduit and wiring installations when mechanical protection is required.

FEATURES AND BENEFITS

• Manufactured under ISO 9001 Quality management systems

ADDITIONAL TECHNICAL SUPPORT

- FAQ's- uk.prysmian.com/technical-area/faqs
- <u>Technical email</u> tech.info@prysmian.com
- Live Chat uk.prysmian.com/technical-area
- Technical hotline: 02380 295222

STANDARDS



BS 7889 BS EN 60332-1-2

CONSTRUCTION

Conductor material Conductor surface Core insulation material Material outer sheath Cable shape Construction Standard Flame Propagation - Single Cable

Copper Bare XLPE Polyvinyl chloride (PVC) Round



APPLICATIONS PROPERTIES

Nominal voltage U0 [V]	600
Nominal voltage U [V]	1,000
Flame retardant	In accordance with BS EN 60332-1-2
Max. conductor temperature [°C]	90
Min. Operation temperature [°C]	-15
UV resistant	Yes
Outdoor installation	Yes
Min. Installation temperature [°C]	0
Max. Installation temperature [°C]	80
Bending radius (rule)	6D

COLOURS

Insulation: Brown or Blue Sheath: Black

CURRENT RATINGS

Refer to table 4El of BS 767l Requirements for Electrical Installations. IET Wiring Regulations Note: Where a conductor operates at a temperature exceeding 70°C it shall be ascertained that the equipment connected to the conductor is suitable for the conductor operating temperature.

Copyright Prysmian, all rights reserved. You may not copy, reprint, or reproduce in any form the content, either wholly or in part, of this document without written consent of Prysmian. All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian. Any modification or alteration of products may cause different results. Prysmian reserves the right to amend the information within this document at any time without notice. For the most up to date information, please contact us. You agree that, in placing any order, you have not relied on the information set out in this document. Prysmian disclaims any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product to the maximum extent permissible by law.



TECHNICAL DATA

Nominal cross section conductor [mm²]	Conductor category	Nominal thickness insulation [mm]	Nominal outer diameter [mm]	Cable weight [kg/km]	Conductor resistance at 20° C [Ohm/km]	Embodied Carbon [CO2e kg/km]
10	Class 2 = stranded	0.7	8.4	150	1.83	476
16	Class 2 = stranded	0.7	9	200	1.15	645
25	Class 2 = stranded	0.9	10.6	295	0.727	851
35	Class 2 = stranded	0.9	11.6	390	0.524	1,078
50	Class 2 = stranded	۱	13.2	520	0.387	1,432
50	Class 2 = stranded	1	13.2	520	0.387	1,432
70	Class 2 = stranded	1.1	14.9	720	0.268	1,895
95	Class 2 = stranded	1.1	16.7	1,000	0.193	2,595
120	Class 2 = stranded	1.2	18.9	1,250	0.153	3,426
120	Class 2 = stranded	1.2	18.9	1,250	0.153	3,426
150	Class 2 = stranded	1.4	21	1,550	0.124	4,114
150	Class 2 = stranded	1.4	21	1,550	0.124	4,114
185	Class 2 = stranded	1.6	23	1,900	0.0991	4,997
185	Class 2 = stranded	1.6	23	1,900	0.0991	4,997
240	Class 2 = stranded	1.7	26	2,500	0.0754	6,413
240	Class 2 = stranded	1.7	26	2,500	0.0754	6,413
300	Class 2 = stranded	1.8	29	3,100	0.0601	7,839
300	Class 2 = stranded	1.8	29	3,100	0.0601	7,839
400	Class 2 = stranded	2	33	3,100	0.047	9,955
400	Class 2 = stranded	2	33	3,100	0.047	9,955
500	Class 2 = stranded	2.2	37	5,000	0.0366	12,683
500	Class 2 = stranded	2.2	37	5,000	0.0366	12,683
630	Class 2 = stranded	2.4	41	6,400	0.0283	16,124
630	Class 2 = stranded	2.4	41	6,400	0.0283	16,124
800	Class 2 = stranded	2.6	46	8,300	0.0221	20,998



TECHNICAL DATA

Nominal cross section conductor [mm²]	Conductor category	Nominal thickness insulation [mm]	Nominal outer diameter [mm]	Cable weight [kg/km]	Conductor resistance at 20° C [Ohm/km]	Embodied Carbon [CO2e kg/km]
1,000	Class 2 = stranded	2.8	51	10,300	0.0176	26,827
1,000	Class 2 = stranded	2.8	51	10,300	0.0176	26,827

*The embodied carbon figure is taken from a single product in the range, for more information on how we calculate our embodied carbon figure visit here:<u>https://uk.prysmiangroup.com/embodied-carbon</u>

Copyright Prysmian, all rights reserved. You may not copy, reprint, or reproduce in any form the content, either wholly or in part, of this document without written consent of Prysmian. All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian. Any modification or alteration of products may cause different results. Prysmian reserves the right to amend the information within this document at any time without notice. For the most up to date information, please contact us. You agree that, in placing any order, you have not relied on the information set out in this document. Prysmian disclaims any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product to the maximum extent permissible by law.