

LSX®

LSOH® Screened Wiring Cable. BS 8436. 300/500 V



Prysmian LSX® is a Low Smoke, Zero Halogen (LSOH®) and flame retardant cable developed to address specific needs of the modern building services and systems

KEY APPLICATIONS

Low voltage circuits typically lighting and power distribution, in buildings.

Suitable for clipped, surface, tray and void installation.

Low smoke, zero halogen and flame retardant.

Ideal for all non-emergency circuits in public buildings.

Fully screened design provides EMC protection for signal clarity.

FEATURES AND BENEFITS

- Fully screened
- Low Smoke, Zero Halogen (LSOH®)
- Manufactured under ISO 9001 Quality management systems

ADDITIONAL TECHNICAL SUPPORT

- FAQ's- uk.prysmian.com/technical-area/faqs
- <u>Technical email</u> tech.info@prysmian.com
- Live Chat uk.prysmian.com/technical-area
- Technical hotline: 02380 295222

STANDARDS



BS 8436 BS EN 60332-1-2 BS EN 61034-2 BS EN 60754-1 Construction Standard Flame Propagation - Single Cable Smoke emission Corrosive and acid gas

GB00_LSX_20251026 P1



CONSTRUCTION

Conductor materialCopperConductor surfaceBareCore insulation materialXLPE

Screen construction Metallised foil

Screen Yes

Screen material Aluminium

Material outer sheath Low smoke zero halogen

Cable shape Round

APPLICATIONS PROPERTIES

Nominal voltage U0 [V] 300 Nominal voltage U [V] 500

Flame retardant In accordance with BS EN 60332-1-2

Halogen free Yes Low smoke Yes Max. conductor temperature [°C] 70 Min. Operation temperature [°C] -15 **UV** resistant Yes Min. Installation temperature [°C] 0 Max. Installation temperature [°C] 60 Bending radius (rule) 6D

COLOURS

Insulation: Two Cores: Brown, Blue; Three Cores: Brown, Black, Grey; Four Cores: Blue, Brown, Black, Grey;

Sheath: White

CURRENT RATINGS

Refer to table 4D2 of BS 7671 Requirements for Electrical Installations. IET Wiring Regulations

Note: When this cable is used to comply with BS 7671: 2018, clause 522.6.204(i), current rating and protective device limitations shall comply with the requirements of BS 8436.

Copyright Prysmian, all rights reserved. You may not copy, reprint, or reproduce in any form the content, either wholly or in part, of this document without written consent of Prysmian. All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian. Any modification or alteration of products may cause different results. Prysmian reserves the right to amend the information within this document at any time without notice. For the most up to date information, please contact us. You agree that, in placing any order, you have not relied on the information set out in this document. Prysmian disclaims any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product to the maximum extent permissible by law.



TECHNICAL DATA

Number of cores	Nominal cross section conductor [mm²]	Conductor category	Colour outer sheath	Nominal cross section of protective conductor [mm²]	Nominal outer diameter [mm]	Cable weight [kg/km]	Conductor resistance at 20° C [Ohm/km]	Embodied Carbon [CO2e kg/km]
2	1.5	Class 2 = stranded	White	1.5	9.9	110	12.1	591
2	2.5	Class 2 = stranded	White	2.5	10.4	150	7.41	759
2	4	Class 2 = stranded	White	4	12.1	200	4.61	981
3	1.5	Class 2 = stranded	White	1.5	10.2	135	12.1	732
3	2.5	Class 2 = stranded	White	2.5	11.1	180	7.41	886
3	4	Class 2 = stranded	White	4	12.3	245	4.61	1,156
4	1.5	Class 2 = stranded	White	1.5	11.1	160	12.1	841
4	2.5	Class 2 = stranded	White	2.5	12.3	220	7.41	1,037
4	4	Class 2 = stranded	White	4	14.3	305	4.61	1,373

^{*}The embodied carbon figure is taken from a single product in the range, for more information on how we calculate our embodied carbon figure visit here: https://uk.prysmiangroup.com/embodied-carbon