

COMM CABLE MULTI-PAIRED UNSHIELDED CM

UL, CSA, NEC approved wires for two way circuits.



PRODUCT CONSTRUCTION:

Conductor: fully annealed stranded tinned copper per ASTM B33

Insulation: Premium-grade, color-coded PVC · Color code: See charts below

Jacket: PVC, gray · Temperature range: -20°C to +105°C · Includes ripcord

Applications: Public address systems · Intercoms · Internal telephones · Suggested voltage rating: 300 or 600 volts

Packaging: Please contact Customer Service for packaging and color options

APPLICATION PROPERTIES

Flame retardant	No	Resistant to UV	No
Halogen free	No	Outdoor installation	No
Low smoke	No	Underground installation	No
Oil resistant	No		

STANDARDS AND APPROVALS



CSA Type AWM (105° C, 600 V) NEC/CEC Type CMG (CSA: 105° C, 300 V)

Passes CSA FT4 vertical flame test

We reserve the right to do changes as a result of running product development and/or changes in standards

ELECTRICAL PROPERTIES

Catalog Number	No. Of. Cond	AWG / Kcmil	Conductor category	Conductor strand count	Insulation thickness [in]	Insulation thickness [mm]	Jacket thickness [in]	Jacket thickness [mm]	Nominal overall o.d.	Nominal outer diameter [mm]
C6360A	12	20	Class 2 = stranded	7/28	0.016	0.41	0.032	0.81	0.354	9
C6702A	4	22	Class 2 = stranded	7/30	0.011	0.28	0.016	0.41	0.155	3.94

We reserve the right to do changes as a result of running product development and/or changes in standards